



WHITEBOARD W 2408 x H 1208 mm white lacquered metal sheet STANDARD

Reference : 411298

Description :

The display panel is essential to promote visual communication. Versatile, it is available in many formats and surface types depending on your use. - Simple and elegant anodised aluminium frame, 24 mm/0.94 Inch wide.

- Fastening at the corners from the front, hidden by plugs.
- CORK BACK PANEL for displaying with pins
- WHITE LACQUERED METAL SHEET for magnetic attaching (one side only)
- ENAMEL 800° for magnetic attachin and lelt writing
- Provided with screws and bolts
- Delivered with bucket for storing felts.STANDARD
- Resistant aluminium back counterbalance.
- PREMIUM
- Counter balancing back in galvanized sheet metal which ensures perfect flatness of the panel over time.

Benefits :

- With a sober and elegant anodized aluminum frame, the panels can easily be used in meeting rooms and offices.
- Very easy to install (only 4 fixing points), can be mounted vertically or horizontally.
- The fasteners are hidden by flaps located on the grey plastic corners that fold down like shells.
- They are available in all sizes from 450 x 600 mm to 1200 x 2400 mm.

- To answer all situations: 3 qualities are available. Cork base for pin display, painted white sheet metal base for magnetic display and 800° enamel base for dry erase felt writing and magnetic display.

Technical specifications :

Product Name	WHITEBOARD W 2408 x H 1208 mm white lacquered metal sheet
	STANDARD
SKU	411298
Weight (kg)	0.000000

GTIN3701484701854Customs code961000000PackagingAssembledThickness (inch)0.59Thickness (mm)15 mmFasteningWall mountedHeight (inch)47.56Height (mm)1208 mmUsable height (inch)45.67Useful height (mm)1160 mmMounting kitIncludedWidth (inch)94.8Width (inch)92.91Usable Width (inch)92.91Useful Width (mm)2360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	Eco-participación	0,38
PackagingAssembledThickness (inch)0.59Thickness (mm)15 mmFasteningWall mountedHeight (inch)47.56Height (mm)1208 mmUsable height (inch)45.67Useful height (mm)1160 mmMounting kitIncludedWidth (inch)94.8Width (inch)92.91Usable Width (inch)92.91Useful Width (inch)92.91Usable Width (inch)92.91Useful Width (inch)92.91Useful Width (inch)1360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	GTIN	3701484701854
Thickness (inch)0.59Thickness (mm)15 mmFasteningWall mountedHeight (inch)47.56Height (mm)1208 mmUsable height (inch)45.67Useful height (mm)1160 mmMounting kitIncludedWidth (inch)94.8Width (inch)92.91Usable Width (inch)2360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	Customs code	961000000
Thickness (mm)15 mmFasteningWall mountedHeight (inch)47.56Height (mm)1208 mmUsable height (inch)45.67Useful height (mm)1160 mmMounting kitIncludedWidth (inch)94.8Width (mm)2408 mmUsable Width (inch)92.91Useful Width (mm)2360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	Packaging	Assembled
FasteningWall mountedHeight (inch)47.56Height (mm)1208 mmUsable height (inch)45.67Useful height (mm)1160 mmMounting kitIncludedWidth (inch)94.8Width (mm)2408 mmUsable Width (inch)92.91Useful Width (mm)2360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	Thickness (inch)	0.59
Height (inch)47.56Height (mm)1208 mmUsable height (inch)45.67Useful height (mm)1160 mmMounting kitIncludedWidth (inch)94.8Width (mm)2408 mmUsable Width (inch)92.91Useful Width (mm)2360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	Thickness (mm)	15 mm
Height (mm)1208 mmUsable height (inch)45.67Useful height (mm)1160 mmMounting kitIncludedWidth (inch)94.8Width (mm)2408 mmUsable Width (inch)92.91Useful Width (mm)2360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	Fastening	Wall mounted
Usable height (inch)45.67Useful height (mm)1160 mmMounting kitIncludedWidth (inch)94.8Width (mm)2408 mmUsable Width (inch)92.91Useful Width (mm)2360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	Height (inch)	47.56
Useful height (mm)1160 mmMounting kitIncludedWidth (inch)94.8Width (mm)2408 mmUsable Width (inch)92.91Useful Width (mm)2360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	Height (mm)	1208 mm
Mounting kitIncludedWidth (inch)94.8Width (mm)2408 mmUsable Width (inch)92.91Useful Width (mm)2360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	Usable height (inch)	45.67
Width (inch)94.8Width (mm)2408 mmUsable Width (inch)92.91Useful Width (mm)2360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	Useful height (mm)	1160 mm
Width (mm)2408 mmUsable Width (inch)92.91Useful Width (mm)2360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	Mounting kit	Included
Usable Width (inch)92.91Useful Width (mm)2360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	Width (inch)	94.8
Useful Width (mm)2360 mmMaterialWhite lacquered metal sheetStructureGrooved anodized aluminumUNSPSC14111607	Width (mm)	2408 mm
Material White lacquered metal sheet Structure Grooved anodized aluminum UNSPSC 14111607	Usable Width (inch)	92.91
Structure Grooved anodized aluminum UNSPSC 14111607	Useful Width (mm)	2360 mm
UNSPSC 14111607	Material	White lacquered metal sheet
	Structure	Grooved anodized aluminum
	UNSPSC	14111607
UNSP5C 21 44111900	UNSPSC 21	44111900